System SF75



☐ Inquiry ☐ Or	der Customer number:
Company stamp / address:	Contact person:
	Telephone:
	Quotation No.:
	Commission:
Opening direction: inwards folding outwards folding	
Number of systems:	
Opening direction: inv	vards folding Outwards folding (Note: Use interior view!)
Number of panel: to t	the left to the right (Please draw a floor plan or a view sketch for better understanding)
Dimensions: Width:	(Total unfolding) Height: (incl. possible floor recession)
Colour: RAL 7016	RAL 9006 RAL 9007 RAL 9016 E6-EV1 Special colour Pre anodizing
Colour of hinges:	☐ E6-EV1 powder ☐ RAL 9011 mat ☐ RAL 9016 ☐ Special colour
Handle colour:	☐ E6-EV1 powder ☐ RAL 9011 mat ☐ RAL 9016 ☐ Special colour
Handle height: H =	(Indicate handle height from lower panel edge)
Glazing:	Standard heat protection glass 2 x 4/20 SZR Ug 1.1 without glass: prepared for mm Special glass: (Please indicate exact designation)
Floor connection:	with weathered bottom track
	with flush bottom track (height incl. floor recession)
Locking of turn panel: (only possible with an add number of panels)	Standard (shoot bolt lock operated from inside only) Shoot bolt lock with PZ (operated from both sides) Roller latch + 2 x dead lock + HEWI push handle Anti-draft lock with mushroom head and 4 point locking, latch and profile cylinder (operable on both sides) Pull handle for turn panel, outward folding system other:
Additional safety:	Twin-Lock RC2-Safety package

Please enclose floor plan resp. view sketch and remarks (please use inside view)