

Inquiry     Order

Customer number: \_\_\_\_\_

Company stamp / address:

Contact person: \_\_\_\_\_

Telephone: \_\_\_\_\_

Quotation No.: \_\_\_\_\_

Commission: \_\_\_\_\_

Number of systems: \_\_\_\_\_

Opening direction:     inwards opening     outwards opening    (Note: Use interior view!)

Parking bay:     Typ 1     Typ 2     Typ 3     Special solution

Number of panel: \_\_\_\_\_ to the left    \_\_\_\_\_ to the right    (Please draw a floor plan or a view sketch for better understanding)

Dimensions:    Width: \_\_\_\_\_ (Total unfolding)    Height: \_\_\_\_\_ (incl. possible floor recession)

Colour:     RAL 7016     RAL 9006     RAL 9007     RAL 9016     E6-EV1     Special colour \_\_\_\_\_  
 Pre anodizing

Handle colour:     E6-EV1 powder     RAL 9011 mat     RAL 9016     Special colour \_\_\_\_\_

Handle height: H = \_\_\_\_\_  (Indicate handle height from lower panel edge)

Glazing:     Standard Insulated glass 2 x 4/20 cavity Ug 3.0  
 without glass: prepared for \_\_\_\_\_ mm  
 Special glass: \_\_\_\_\_ (Please indicate exact designation)

Ceiling connection:     without overlay profile     with overlay profile inside     with overlay profile outside

Ground connection:     with floor sockets     with flush bottom track (height incl. floor recession)  
 with recessed bottom track and lowerable bottom door seal (height incl. floor recession)

Locking of turn panel:     Standard (shoot bolt lock operated from inside only)  
 Shoot bolt-lock with PZ (operated from both sides)  
 Mortise door lock with PZ (operated from both sides)  
 Roller latch + 2 x dead lock + HEWI push handle  
 Anti-draft lock with mushroom-lock, latch and PZ (operated from both sides)  
 other: \_\_\_\_\_

Turn panel:     without     Integrated turn-panel in panel-No.: \_\_\_\_\_  
 with overhead door closer, push handle, 2 x dead lock  
 with mortise door lock with PZ and handle at both sides

(The panel No. is counted from the left to the right.  
Please draw opening direction into the sketch.)

Please enclose floor plan resp. view sketch and remarks (please use inside view)