## System SF55 H-S-W



☐ Inquiry ☐ Order	Customer number:
Company stamp / address:	Contact person:
	Telephone:
	Quotation No.:
	Commission:
Number of systems:	
Opening direction: inwards opening outwards opening	ng (Note: Use interior view!)
Parking bay: Typ 1 Typ 2 Typ 3	Special solution
Number of panel: to the left to the right (Please draw a floor plan or a view sketch for better understanding)	
Dimensions: Width: (Total unfolding)	Height: (incl. possible floor recession)
Colour: RAL 7016 RAL 9006 RAL 9007 RAL 9016 E6-EV1 Special colour Pre anodizing	
Handle colour: E6-EV1 powder RAL 903	L1 mat RAL 9016 Special colour
Handle height: H = (Indicate handle height from lower panel edge)	
Glazing:  Standard Insulated glass 2 x 4/20 cavity Ug 1.1 without glass: prepared for mm Special glass: (Please indicate exact designation)	
Ceiling connection: without overlay profile with overlay profile inside with overlay profile outside	
Ground connection: with floor sockets with flush bottom track (height incl. floor recession)	
Locking of turn panel:  Standard (shoot bolt lock operated from inside only)  Shoot bolt-lock with PZ (operated from both sides)  Mortise door lock with PZ (operated from both sides)  Roller latch + 2 x dead lock + HEWI push handle  Anti-draft lock with mushroom-lock, latch and PZ (operated from both sides)  other:	
	r, push handle, 2 x dead lock th PZ and handle at both sides oft to the right.

Please enclose floor plan resp. view sketch and remarks (please use inside view)